

# SC517/WH/MULTI/G2/EN

## Surface Contact



- 4 Terminals
- Microswitch tamper
- Selectable end of line resistor
  - Can use own resistors
  - Available in White or Brown
  - Can be fitted in double pole
  - Can be used on double door configuration

Connections	<b>4 Terminals</b>	Switching Current	<b>500mA @ 12Vdc</b>
Reed Switches	<b>1</b>	Contact Material	<b>Rhodium</b>
Pull-in Gap	<b>25mm (X) 15mm (Y)</b>	Temperature Range	<b>-15° C to +40° C</b>
Material	<b>High Impact Polystyrene</b>	Tamper	<b>Microswitch</b>
Contact Size mm	<b>65 x 13 x 13</b>	Colours	<b>White/Brown</b>
Magnet Size mm	<b>65 x 11 x 13</b>	Magnetic Interference Detection	<b>N/A</b>
Contact Form	<b>SPST form A</b>	Standards	<b>EN50131-2-6 Grade 2</b>
Voltage Range	<b>12v DC</b>	Environmental Class	<b>II</b>



FireBrand — **2Y-LINK** — CQR MAXIMAL

**CQR Fire & Security**  
125 Pasture Road, Moreton, Wirral, CH46 4TH, UK

