

DS778 Long Range PIR Detector

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Motion Analyzer II processing
- ▶ Pointable mirrored optics
- ▶ Q-map signal processing
- ▶ Long range coverage
- ▶ Four mounting options

The wall mount, long range DS778 PIR Detector uses Motion Analyzer II signal processing to reduce false alarms. To aid in walk testing, the DS778 features a high efficiency alarm LED that is visible throughout the coverage pattern. This allows one installer to install and test the detector. The detector's internally pointable optics and mounting options provide installation flexibility.

Functions

Signal Processing

Motion Analyzer II uses multiple thresholds and timing windows to analyze timing, amplitude, duration, and polarity of signals to make an alarm decision. Will not alarm on extreme levels of thermal and illumination disturbances caused by heaters and air conditioners, hot and cold drafts, sunlight, lightning, and moving headlights. Two sensitivity settings are provided.

Test Features

The high efficiency alarm LED can be seen throughout the walk test area. Internal noise voltage test pins provide precise pattern location and background disturbance evaluation using a standard analog meter.

Insect and Draft Immunity

The sealed optical chamber provides immunity to drafts and insects.

Certifications and approvals

Europe Complies with EN50131-1, Grade 2

Region	Certification	
Europe	CE	2004/108/EC EMC Directive (EMC); 2006/95/EC Low-Voltage Directive (LVD) [DS778]
USA	UL	ANSR: Intrusion Detection Units (UL639)

Installation/configuration notes



Top View

Long Range Coverage 60 m x 4.5 m (200 ft x 15 ft)



Side View**Long Range Coverage 60 m x 4.5 m (200 ft x 15 ft)****Technical specifications****Enclosure Design**

Dimensions:	14.6 cm x 9.5 cm x 6.35 cm (5.75 in. x 3.75 in. x 2.5 in.)
Material:	High impact ABS plastic enclosure

Environmental Considerations

Operating Temperature:	-40°C to +49°C (-40°F to +120°F) <i>For UL Listed Applications, 0°C to +49°C (+32°F to +120°F)</i>
Radio Frequency Interference (RFI) Immunity:	No alarm or setup on critical frequencies in the range from 26 MHz to 950 MHz at 50 V/m.

Complies with Environmental Class II (EN50130-5)

Mounting

Height Range:	Recommended 2 m to 2.6 m (6.5 ft to 8.5 ft)
Internal Pointability:	Coverage is adjustable $\pm 10^\circ$ horizontally, $+2^\circ$ to -18° vertically.

Outputs

Alarm:	Form C contacts rated at 3.0 W, 125 mA at 28 VDC for resistive loads.
Tamper:	Normally-closed. Contacts rated at 28 VDC, 125 mA maximum.

Power Requirements

Current Draw:	18 mA at 12 VDC
Voltage:	6 VDC to 15 VDC

Ordering information**DS778 Long Range PIR Detector**

Provides Motion Analyzer II processing, movable mirrors, Q-map signal processing, long range coverage, and four mounting options.

Order number **DS778****Accessories****B328 Gimbal-mount Bracket**

Mounts on a single-gang box and allows rotation of a detector. Wires are hidden inside.

Order number **B328****Swiveling B335-3 low-profile mount**

Swiveling, low-profile, plastic mount for wall mounting. The vertical swivel range is $+10^\circ$ to -20° , while the horizontal swivel range is $\pm 25^\circ$. Available in triple packs.

Order number **B335-3****B338 Universal Ceiling-mount Bracket**

Swiveling plastic mount for ceiling mounting. The vertical swivel range is $+7^\circ$ to -16° , while the horizontal swivel range is $\pm 45^\circ$.

Order number **B338****TC6000 Test Cord**

Test cord for connecting a compatible detector's test pins to a voltmeter. It is 4.6 m (15 ft) long.

Order number **TC6000**

Represented by:

Americas:

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security
Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com