



VEGA

VMxC120 Single Output Module



- VMC120** Wall Mounting Single Output Module.
- VMMC120** Mini Single Output Module.
- VMDC120** Din Rail Single Output Module.


SPECIFICATIONS

Vega analogue devices are designed around a fully digital protocol.


One output loop powered unsupervised module is based on a SPDT relay ("form C").

The relay is normally de-energized. It is switched on by special command from the control panel.

It is available on different shapes useful for different installation requests.



CERTIFIED
EN54-18:2005
by BSI
KMXXXXX



0086

Argus Security Srl,
Via Archimede 42,
20041 Agrate Brianza, Milan, Italy

08
0086 - CPD - 533485

EN54-18:2005
Form C contacts output (mini) module
VMC120 - VMMC120
Technical data: see Document
TDS-MC120
held by the manufacturer

FEATURES & BENEFITS

- Designed to meet the standard EN54-18
- Provide high reliability and error detection
- Short circuit isolators in each device
- Large capacity, up to 240 devices per loop
- Addressable by a special tool
- Auto addressing capability (Control panel feature)
- OEM password protection
- High power availability from loop (>98%),
- Digital checking of double address
- Line quality information
- Bicolour (red green) LED driven by the control panel

TECHNICAL SPECIFICATIONS	
Power Supply	15-40 V
Average Current Consumption	$I = 120\mu A$
LED current consumption	$I_{led} = 6mA @ 24V_{dc}$
Operating Temperature Range	-30°C / +70°C
Humidity (no condensation)	95% RH
Relay characteristic	$I = 2A \quad v = 30V_{dc}$



